

TECNO[®]

Accessori

Scheda Tecnica Lettore Barcode Laser 1D TECNOACCESSORI[®]

TC-BCW-700

2.4G Wireless laser barcode scanner



Features

1. Factory direct sale, cheap price and stable scanning
2. Fast and accurate in reading 1D codes
3. Service life of button reaches up to 5 million times.
4. Multiple interface, support USB (standard), RS232 (optional), PS/2 (optional).
5. No need driver, plug and play

Specifications	
Light Source	650nm laser (safe visible light)
Operating Channel	433MHz SM
Communication Distance	150m indoor; 300m outdoor
Supported Symbolologies	Code 39, full ASCII, code bar, industrial 2 of 5, interleave 2 of 5, matrix 2 of 5, code 93, code 128, code 32, standard code 93, EAN 128, MSI, EAN8&13, UPCA&E, Plessey, DataBar14, Telepe and all 1D barcodes
Precision	≥4 mil (0.1mm)
Depth of Scan Field	10-800mm
Supported interfaces	USB (standard), RS232 (optional), PS/2 (optional)
Operation	Manual
Decode Speed	120times/second
Light Intensity	Daylight, 4000Lux
Decode Error Rate	less than 1/5 million
Print Contrast Signal	≥30°
Scan Angel	Yaw(Skew) 45° Pitch 60°
Safety	Full quakeproof, dustproof, antiknock-design and EMI Shielding

Mechanical/Electrical

Optional:



Applicable scope

- ✓ Comercial POS system(Supermarkets)
- ✓ Warehousing and logistics
- ✓ Libraries
- ✓ Banks and Telecom
- ✓ Transportaion
- ✓ Postal service
- ✓ Industrial and manufacturing management

Packing list

scanner × 1

Receiver × 1

User's guide × 1

cable × 1



Packing details

scanner	Size(L*W*H)	169mm*70mm*90mm
	Weight	235g;
	Without Stand	With Stand
Inner Box	1pc/box; 190mm × 115mm × 85mm; 320g	1pc/box; 210mm × 130mm × 100mm; 520g

Voltage	5V
Current	Operation 68mA; Idle 48mA
Scanner Material	Eco-friendly, ABS
Environment	
Operation Temperature	-20°-45°
Storage Temperature	-20°-45°
Humidity	5%-85%



A causa di countinua evoluzioni tecniche del prodotto , le caratteristiche possono subire variazioni senza preavviso

Certifications

FC

CE

RoHS