

Scheda Tecnica Telecamera TECNOACCESSORI®

modello TC-4016WF-IP



Specifications:

Wide Angle Pan Tilt Camera Easy to Operate: The wireless camera is a Mini PT camera with small size and light weight. But it can monitor your object very widely: 0-355° pan moving and 0-90° tilt moving are combined with amazing clarity (1080P 4mm lens), monitoring in real time with wide angles and clear pictures. And you can operate it with your smart phone App very Easily.

Max Support 128GB TF Card: this wifi security camera recordings to enjoy peace of mind any time from anywhere with the Micro TF Card. Waterproof micro TF slot allows for free local recording. It supports micro TF card up to 128G if needed and the oldest videos will be over record automatically when the storage is full.

1080P High Definition & Super Night Vision: This wireless camera presents very clear HD picture in daytime and it uses a Sony sensor to deliver unparalleled night vision for great clarity of detail up to 20m with automatic-control infrared lights. And you can manually turn on the white light setting in the dark environment to see color full image if you like.

IP66 Waterproof Outdoor & Indoor Usage: This home surveillance camera is made with weatherproof shell which makes it durable and won't rust. With IP66 rate Waterproof, it can be placed both indoors and outdoors, and perfect to be mounted on wall, for home surveillance & office security, for baby & pet monitor, etc.

Main Features:

2.0 megapixels 1080P HD resolution 1920x1080, excellent video and image quality.

Built-in windproof TF card slot, easy to expand and replace memory TF card.

translation and tilt and zoom: translation 355 degrees, tilt 90 degrees

Embedded with 8 powerful array LEDs, it can achieve 10m night mode.

IP66 waterproof grade, windproof.

Remote access and control to iOS and Android App.

Motion detection alert notifications are sent by application or e-mail to record images and videos to TF cards or devices.

Support Onvif / P2P, CMS / Motion Detection / Alarm Push / Email Alarm / FTP

Built-in Speaker , support two way audio talk

Storage: Support max 128G local storage.

Model		TC-4016WF-IP
Camera	Operating system	Embedded Linux OS
	Megapixel	1920*1080
	Lens	4mm Fixed Lens(no support zoom)
	View angle	90deg
	Min.illumination	0.05 Lux / 0 Lux(IR on)
	Day&Night mode	Auto IR-CUT
	Night vision distance	8pcs Array Infrared LEDs , 30m Night Vision
Video	Video compression standard	H.264 Main Profile/H.264 Baseline
	Video resolution	First stream: 1080P(1920x1080), 720P(1280x720)
		Second stream: Q720P(640x480/640x352), QQ720P(320x240/320x176)
		JPEG stream :(Monitoring for mobile phones), Q720P(640x352), QQ720P(320x176)
	Image enhancement	Backlight compensation,Automatic white balance,Digital WDR, 3D digital noise reduction
Audio	Audio compression standard	G.726/G.711
	Audio Input	Support, Built-in Microphone
	Audio Output	Support Two Way Audio Talk , Built-in Loud Speaker
Function	Alarm linkage	Alarm send pictures to the specified mailbox, alarm upload pictures and videos to the FTP server, alarm write pictures and videos to Micro TF card, alarm message push
	Privacy mask	Maximum support 5 users to simultaneously browse
	Simultaneous viewers	maximum support 12 users to simultaneously browse (each stream supports 5 users)
	Network protocol	TCP/IP,HTTP,TCP,ICMP,UDP,ARP,IGMP,SMTP, FTP,DHCP,DNS,DDNS,NTP,UPNP,RTSP etc.

	Connection protocol	Support ONVIF 2.4(backward compatible)
Wireless	Wireless standards	IEEE802.11b. 802.11g. 802.11n Draft
	Frequency range	2.4 GHz
	Wireless Security	WPA/WPA2. WPA-PSK/WPA2-PSK. WPS
PTZ	Rotation angle	Horizon:0° to 355°. Vertical: 0° to 90°
	Ethernet	1*RJ45 & Antenna 10M/100M Adaptive Ethernet Interface
	TF card Slot	1*TF card slot. up to 128G(Don't included TF Card)
	Reset button	Support
General Specificatio n	Power supply	DC 12V 2A
	Operating temperature	-20 to +50 degree
	Operating humidity	10% to 95%



A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni