



# TECNO®

Accessori

## Linea Videosorveglianza

Modello

SCHEDA TECNICA DVR TECNO® MODELLO TC-5IN1-04 cod. prodotto 59.91

Foto



**Funzioni**

1. TVI / AHD / CVI / IPC / Analog 5 in 1.
2. Transmission distance upto 500M by coaxial cable 75-5(or above)
3. Support P2P ([www.vssweb.net](http://www.vssweb.net))
4. Support mobile surveillance (**APP: VSS Mobile**)
5. Support UTC function : Control AHD/TVI Camera & PTZ Sped Dome camera via DVR by Coaxial Cable
6. Support **Cloud Storage (Dropbox / Google Drive)**
7. Advanced time bar playback function can make playback exact to a second
8. Digital zoom function in both preview & playback
9. Support **Built-in free DDNS**
10. Support **mobile hard disk backup**
11. Support **3G wireless Dongle**
12. Support **Alarm Function**

**Sistema**

Chips	<b>Hi3520D V200</b>
Operation System	Embedded LINUX
Pentaplex function	Live monitoring, recording, playback, backup & remote access
Control Mode	Front panel, USB/Wireless mouse, IR remote, Network

**Video**

Input	<b>Hybrid input(Mix freely): TVI / AHD / CVI (720/960/1080P) + IP (720/960/1080P) + CVBS(960H)</b>
Standard	PAL / NTSC
Output	1 CVBS, BNC 1 HDMI, 1920x1080,1280x1024,1366x768,1280x720,1024x768 Resolution 1 VGA, 1920x1080,1280x1024,1366x768,1280x720,1024x768 Resolution
UTC	Control AHD/TVI Camera & PTZ Sped Dome camera via DVR by Coaxial Cable

**Audio**

Input	4ch RCA 4ch by RJ45(for IPC)
Output	1ch RCA

**Registrazione**

Video Compression	H.264
Audio Compression	G.711A
Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream
Dual Stream	Support
Recording Mode	Manual, auto, motion detection, stop
Time bar	Support

**Video Detection&Alarm**

Trigger Events	Recording, PTZ, Tour,Email
Motion Detection	396 (22x18) detection zone, variable sensitivity levels
Capture	JPEG capture
Alarm In/Output	4ch in,1ch out (Support)
Face Detection	no
Perimeter Detection	no

**Playback&Backup**

Max Playback	IP : 1~2ch 720/1080P @ 25/30fps AHD / TVI / CVI : 1~4ch 1080N @ 12fps
Backup Mode	USB,HDD,Network Backup,Mobile Harddisk

**Network**

Ethernet	1 RJ-45 port (10M/100M)
P2P	Support
Cloud Storage	Support
DDNS	Support Built-in Free DDNS
3G Dongle	Support
Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
Network Functions	DHCP, PPPoE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
Remote Operation	Monitoring,PTZ control,playback.system setting,file download,log information
Smart Phone	iPhone,iPad,Android

**Hard Disk**

Hard Disk	1 SATA (Max: 8TB/HDD)
HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid

**Auxiliary Interface**


USB Interface	2 USB 2.0 ports
RS485	PTZ control
Power Supply	DC 12V

**Environment**

Power Consumption	<9W (without HDD)
Working Environment	-10°C~ +55°C / 10%~90%RH
Dimension(W*D*H)	Machine: 280x225x45mm Color Box:380x270x80mm
Weight	1.5 Kg (without HDD)
Installation	Desk type

**TECNO® 4CH H.264 5 in 1 Network Digital Video Recorder**  
Accessori **Model NO.: TC-5IN1-04**

4ch video & 4ch audio Support Alarm function  
Hybrid: TVI / AHD / CVI (720/960/1080P)+IP(720/960/1080P)+CVBS(960H)  
Support UTC function  
UPNP (Universal Plug & Play) **RoHS**  
Built-in free DDNS ( FNT DDNS ) compliant  
P2P([www.vssweb.net](http://www.vssweb.net)) **CE**  
Digital zoom in preview & playback  
3G dongle supported  
Mobile Phone APP (VSS Mobile) **FCC**  
SATA: 1xHDD Power: DC 12V 3A  
Prodotto Importato e distribuito dal rispettivo proprietario del Marchio TECNO



MADE IN CHINA



A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni senza preavviso!