



TECNO®
Accessori
Linea Videosorveglianza

MODELLO	SCHEDA TECNICA DVR TECNO® MODELLO TC-5IN1FACE16 Cod. prodotto 50.93
FOTO	

FUNZION I	<ol style="list-style-type: none"> 1. TVI / AHD / CVI / IPC / Analog 5 in 1. 2. Transmission distance upto 500M by coaxial cable 75-5(or above) 3. Support P2P (www.vssweb.net) 4. Support mobile surveillance (APP: VSS Mobile) 5. Support UTC function: Control AHD/TVI Camera & PTZ Spped Dome camera via DVR by Coaxial Cable 6. Support Cloud Storage (Dropbox / Google Drive) 7. Advanced time bar playback function can make playback exact to a second 8. Digital zoom function in both preview & playback 9. Support Built-in free DDNS 10. Support mobile hard disk backup 11. Support 3G wireless Dongle 12. Support Face Detection & Perimeter Detection
------------------	--

System	Chips	Hisi3521A
	Operation System	Embedded LINUX
	Pentaplex function	Live monitoring, recording, playback, backup & remote access
	Control Mode	Front panel, USB/Wireless mouse, IR remote, Network

Video	Input	Hybrid input(Mix freely): TVI / AHD / CVI (720/960/1080P) + IP (720/960/1080P/3.0/4.0/5.0MP) + CVBS(960H)
	Standard	PAL / NTSC
	Frame Rate	Live Preview: PAL: 1~25fps; NTSC: 1~30fps
	Output	1 CVBS, BNC 1 HDMI, 1920x1080, 1280x1024, 1366x768, 1280x720, 1024x768 Resolution 1 VGA, 1920x1080, 1280x1024, 1366x768, 1280x720, 1024x768 Resolution
	UTC	Control AHD/TVI Camera & PTZ Spped Dome camera via DVR by Coaxial Cable

Audio	Input	4ch RCA 16ch by RJ45(for IPC)
	Output	1ch RCA

Record & Playback	Video Compression	H.264
	Audio Compression	G.711A
	Image Encoding	Adjustable encoding quality, variable code stream/fix code stream
	Dual Stream	Support
	Recording Mode	Manual, auto, motion detection, stop
	Time bar	Support
	Max Playback	IP : 1~8ch 720/1080P @ 25/30fps AHD / TVI / CVI : 1~16ch 1080N @ 12fps
	Backup Mode	USB,HDD,Network Backup,Mobile Harddisk

Video Detection& Alarm	Trigger Events	Recording, PTZ, Tour,Email
	Motion Detection	396 (22x18) detection zone, variable sensitivity levels
	Capture	JPEG capture
	Alarm In/Output	N/A
	Face Detection	Support
	Perimeter Detection	Support
	Ethernet	1 RJ-45 port (10M/100M/1000M)

Network	P2P	Support
	Cloud Storage	Support
	DDNS	Support Built-in Free DDNS
	3G Dongle	Support
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP
	Network Functions	DHCP, PPPOE, DDNS,SMTP,SNTP,FTP,UPnP,P2P,3G
	Remote Operation	Monitoring,PTZ control,playback,system setting,file download,log information
	Smart Phone	iPhone,iPad,Android

Hard Disk	Hard Disk	1 SATA (Max: 8TB/HDD)
	HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid


Auxiliary Interface	USB Interface	2 USB 2.0 ports
	RS485	PTZ control

Environment	Power Supply	DC 12V
	Power Consumption	<9W (without HDD)
	Working Environment	-10℃~+55℃ / 10%~90%RH
	Dimension(W*D*H)	Machine: 280x225x45mm Color Box:380x270x80mm
	Weight	1.5 Kg (without HDD)
	Installation	Desk type

TECNO® 16CH H.264 5 in 1 Network Digital Video Recorder
Accessori **Model NO.: TC-5IN1FACE16**


16ch video & 1ch audio Support Face Detection
Hybrid: TVI / AHD / CVI (720/960/1080P)+IP(720/960/1080P)+CVBS(960H)

Support UTC function
UPNP (Universal Plug & Play)
Built-in free DDNS (FNT DDNS)
P2P(www.vssweb.net)
Digital zoom in preview & playback
3G dongle supported
Mobile Phone APP (VSS Mobile)



0 921233 333379

SATA: 1xHDD Power: DC 12V 3A
Prodotto Importato e distribuito dal rispettivo proprietario del Marchio TECNO



2017080601 MADE IN CHINA



Made in P.R.C.

A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni senza preavviso!