



**TECNO**<sup>®</sup>  
Accessori  
**Linea Videosorveglianza**

MODELLO

**SCHEDA TECNICA DVR TECNO® MODELLO TC-5IN1FACE08 cod. prodotto 59.91**

FOTO PRODOTTO



**FUNZIONI**

1. TVI / AHD / CVI / IPC / Analog 5 in 1.
2. Transmission distance upto 500M by coaxial cable 75-5(or above)
3. Support P2P ([www.vssweb.net](http://www.vssweb.net))
4. Support mobile surveillance (**APP: VSS Mobile**)
5. Support **UTC** function: Control AHD/TVI Camera & PTZ Spped Dome camera via DVR by Coaxial Cable
6. Support **Cloud Storage** (**Dropbox / Google Drive**)
7. Advanced time bar playback function can make playback exact to a second
8. Digital zoom function in both preview & playback
9. Support **Built-in free DDNS**
10. Support **mobile hard disk backup**
11. Support **3G wireless Dongle**
12. Support **Face Detection & Perimeter Detection**
13. Support **Alarm Function**

<b>System</b>	Chips	<b>His3520D V300</b>	
	Operation System	Embedded LINUX	
	Pentaplex function	Live monitoring, recording, playback, backup & remote access	
	Control Mode	Front panel, USB/Wireless mouse, IR remote, Network	
<b>Video</b>	Input	<b>Hybrid input(Mix freely): TVI / AHD / CVI (720/960/1080P) + IP (720/960/1080P) + CVBS(960H)</b>	
	Standard	PAL / NTSC	
	Output	1 HDMI, 1920x1080,1280x1024,1366x768,1280x720,1024x768 Resolution 1 VGA, 1920x1080,1280x1024,1366x768,1280x720,1024x768 Resolution	
	UTC	Control AHD/TVI Camera & PTZ Spped Dome camera via DVR by Coaxial Cable	
<b>Audio</b>	Input	4ch RCA 8ch by RJ45(for IPC)	
	Output	1ch RCA	
<b>Recording</b>	Video Compression	H.264	
	Audio Compression	G.711A	
	Image Encoding	Adjustable encoding quality, variable code stream/fixed code stream	
	Dual Stream	Support	
	Recording Mode	Manual, auto, motion detection, stop	
<b>Video Detection&amp;Alarm</b>	Time bar	Support	
	Trigger Events	Recording, PTZ, Tour,Email	
	Motion Detection	396 (22x18) detection zone, variable sensitivity levels	
	Capture	JPEG capture	
	Alarm In/Output	4ch in,1ch out (Support)	
<b>Playback&amp;Backup</b>	Face Detection	Support	
	Perimeter Detection	Support	
	Max Playback	IP : 1~4ch 720/1080P @ 25/30fps AHD / TVI / CVI : 1~8ch 1080N @ 12fps	
	Backup Mode	USB,HDD,Network Backup,Mobile Harddisk	
	Ethernet	1 RJ-45 port (10M/100M)	
<b>Network</b>	P2P	Support	
	Cloud Storage	Support	
	DDNS	Support Built-in Free DDNS	
	3G Dongle	Support	
	Network protocol	TCP/IP, UDP, HTTP, RTP/RTSP	
	Network Functions	DHCP, PPPOE, DDNS, SMTP, SNTP,FTP,UPnP,P2P,3G	
	Remote Operation	Monitoring,PTZ control,playback,system setting,file download,log information	
	Smart Phone	iPhone,iPad,Android	
<b>Hard Disk</b>	Hard Disk	1 SATA (Max: 8TB/HDD)	
	HDD Management	Hard disk hibernation technology, HDD faulty alarm&raid	
<b>Auxiliary Interface</b>	USB Interface	2 USB 2.0 ports	
	RS485	PTZ control	
<b>Environment</b>	Power Supply	DC 12V	
	Power Consumption	<9W (without HDD)	
	Working Environment	-10°C ~ +55°C / 10%~90%RH	
	Dimension(W*D*H)	Machine: 280x225x45mm Color Box:380x270x80mm	
	Weight	1.5 Kg (without HDD)	
	Installation	Desk type	

**TECNO**<sup>®</sup> 8CH H.264 5 in 1 Network Digital Video Recorder  
Accessori  
Model NO.: **TC-5IN1FACE08**

8ch video & 4ch audio Support Alarm function  
Hybrid: TVI / AHD / CVI (720/960/1080P)+IP(720/960/1080P)+CVBS(960H)  
Support UTC function Support Face Detection  
UPNP (Universal Plug & Play) RoHS compliant  
Built-in free DDNS ( FNT DDNS )  
P2P([www.vssweb.net](http://www.vssweb.net))  
Digital zoom in preview & playback  
3G dongle supported  
Mobile Phone APP (VSS Mobile)

SATA: 1xHDD Power: DC 12V 3A  
Prodotto Importato e distribuito dal rispettivo proprietario del Marchio TECNO



MADE IN CHINA



A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni senza preavviso!