

Scheda Tecnica DVR TECNOACCESSORI[®] MODELLO TC-8CH 5MP-N



Feature:

- Support H.265+ encoding, ultra-low bitrates, compatible with H.264 surroundings
- Support CVBS, VGA, HDMI full HD output simultaneously
- Support ONVIF;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, VMS, center platform management software MYEYE
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal & video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP six signals
- Support intelligent analysis: Human detection,

Specification:

	Model	8CH 5MP-N
System	Main processor	NT98331
Interface	Preview	1/4/8/9
Video	Codec	H.265+
	Monitor quality	CVBS: VGA(1080P at most);HDMI(2K at most)
	Preview ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps (6 in 1) / 8*1080P@15fps (XVI), default:5M-N
	Encode ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps (6 in 1) / 8*1080P@15fps (XVI), default:5M-N
	Decode ability	8*5M-N@12fps(6 in 1)/ 8*4M-N@15fps (6 in 1) / 8*1080P@15fps (XVI), default:5M-N
	Multi-mode input	Analog: 8*5M-N hybrid: 8*5M-N (analog) +4*1080P (network) Network: 16*1080P; 8*5M
		Motion Detection

		sensitivity can be set (Limited local channel)
Audio	Coaxial audio	support
	Audio compression	G.711A
	Intercom	support
Record & playback	Record mode	manual>alarm>motion detection>timing
	Local Playback	4ch(analog input mode)
	Search mode	Search by time, calendar, event, channel
Storage & backup	Video storage	HDD, network
	Backup mode	Network, USB hard disk, USB burner, SATA burner
External Interface	Video input	8ch BNC
	Video output	1ch VGA, 1ch HDMI
	Audio I/O	4/1
	Alarm I/O	4/1
	Network interface	RJ45 10M/100M self-adaption
	PTZ control	Support kinds of PTZ protocols
	USB	2* USB 2.0 ports
	HDD	2*SATA ports (Max 14TB/per)
	Wireless	3G, WIFI (extend via USB)
General	Power supply	12V/2A
	Power Consumption	<15W (without HDD)
	Working environment	Temperature:0°C—+55°C, Humidity:10%—90%, Atm:86kpa—106kpa
	Dimension	170mm*60mm
	Weight	124g

Prodotto Importato e Distribuito dalla TECNOACCESSORI®

A causa dei continui aggiornamenti si potrebbero riscontrare differenze nei dati tecnici sopra elencati.

