

SCHEDA TECNICA

Lettore Barcode Laser 1D/2D TECNOACCESSORI[®] TC-BC2D-09

	USB (USB-KBW, USB-COM)
Image sensor	CMOS
pixels	300000 pixels
Resolution	≥4mil/0.1mm (PCS90%,CODE 39)
Decoding speed	25CM/S
Reading patterns	Manual reading, induction reading, continuous reading
Tips	LED light, buzzer (external circuit)
View angle	36°*28°
Read angle	<i>Test Conditions: CODE39,10mil/0.25mm,PCS90%</i>
Print Contrast	Rotation Roll: ±360, Tilt Pitch: ±50, Skew: ±50
Ambient illumination	≥25%
Reading Code	Dark environment , indoor natural light

Communications 1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Standard 2 of 5(IATA25), Codabar (NW-7), etc.

2D: QR Code, Micro QR Code, Data Matrix, PDF417,, etc.

Electrification Performance

	< 105g (excluding wire)
Appearance	Length 175 mm * W 50 mm * H 37 mm
Communication	USB(USB-KBW、USB-COM)
Length of wire	1.5 m (charging line)
Material	ABS
Color	Black
Working voltage	DC 5V
Current	90mA (operation)

Working Environment

Storage	-40°C to 60°C
Working	5% to 95% (No condensation)
Transport	10H@125RPM



Made In China

A causa di continua evoluzioni tecniche del prodotto , le caratteristiche possono subire variazioni senza Preavviso.

Prodotto Importato e distribuito dal rispettivo Proprietario del Marchio TECNOACCESSORI®