

TECNO®

Accessori

Scheda Tecnica Lettore Barcode Laser 1D/2D

TECNOACCESSORI® TC-BC2D-04W

Mechanical and Electrical Parameter	
Weight	415g with cradle
Size(Length x Width x Height)	184×74×93mm
Material	ABS+PC+TPU
Interface	USB
Working Voltage	5V
Operating Current	70mA
Standby Current	36mA
Scan Performance Parameter	
Optical Source	Visible red light 625nm±10nm, white LED
Image Sensor	CMOS
Scan speed	300times/s
Indicator	buzzer, light (LED)
Scan depth	0-400mm
Print Contrast	≥ 20%
Resolution	≥ 4mil
Scan Angle	Tilt ±30°; Rotate ±65°; Deflection ±60°
Scan mode	Manual/Auto-sense
Scan Width	30mm @ scan window, 220mm @ 200mm
Decode Capabilities	1D: UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code 39, Code 39, Full ASCII) , Code 32, Code 39-Trioptic, Code 25-Interleaved, Code 25-Industria, Code 25-Matrix, Codabar (NW7) , Code 128, Code 93, Code 11 (USD - 8) , MSI/Plessey, UK/Plessey, UCC/EAN 128, China Post Code, GS1 databar 2D: QR, PDF417, Aztec, DataMatrix, Micro PDF417, Maxicode
Connectivity	USB cable(1.5m), 2.4G+Bluetooth (embedded in the cradle)
Transmission distance	2.4G 60 meters/Bluetooth 10 meters
Storage capacity	4M
Battery capacity	Chargeable lithium battery 2200mAH

Charge time	3.5 hours
Working time	8 hours plus (under continuous scan mode) ;12 hours (manual trigger mode)
Environmental Parameter	
Ambient brightness	0-10000lux (daylight)
Working temperature	-20°C-50°C
Storage temperature	-40°C-60°C
Humidity	5%-95% (No condensation)
Drop Resistance	Withstands multiple times 10m drops to concrete
IP Rating	IP65 (IP68 can be customized)



A causa di countinua evoluzioni tecniche del prodotto , le caratteristiche possono subire variazioni senza preavviso