

TECNO®

Accessori

Scheda Tecnica Lettore Barcode Laser 1D/2D

TECNOACCESSORI® TC-BC2D-05

Mechanical and Electrical Parameter

Weight	125g
Size(Length x Width x Height)	90mm*74mm*172mm
Material	APS+PC
Connectivity	USB cable(1.8 meters, Free Drive), Serial port(optional)
Input Voltage	DC 5V±5%
Operating Current	168mA
Standby Current	80mA
Maximum current	293mA

Scan Performance Parameter

Light source	Wavelength of 675nm ± 3nm high brightness near infrared LED
Sensor	960*640 COMS
Scan speed	300 Times/Second
Scan mode	Manual key scan、 Automatic continuous scan
Indicator	buzzer, light (LED)

Scan depth	Tested Code	Minimum	Maximum
	15.6mil EAN-13	5CM	34CM
15mil QR	4CM	15CM	
15mil PDF417	4CM	21CM	
13mil UPC	4CM	28CM	
7.8mil Code 39	15CM	21CM	

Print Contrast	20%
Resolution	4mil
Scan Angle	Horizontal : 72° Vertical: 82° Rotated:360°
System support	Linux、 Android、 Windows XP、 7、 8、 10、 Mac

Keyboard support	Support multi-language keyboard
Decode Capabilities	1D: EAN-8, EAN-13, EAN-13 2 add-on, EAN-13 5 add-on, ISSN, ISBN, UPC-A, UPC-E, Code 11, Code 32, Code 39, Code 93, Code 128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5 2D: PDF417, MicroPDF417, QR-code, Micro QR, Data Matrix, QR, Aztec
Environmental Parameter	
Working temperature	-20-55°C
Storage temperature	-20-60°C
Humidity	5%-95% (Non-condensation)



A causa di countinua evoluzioni tecniche del prodotto , le caratteristiche possono subire variazioni senza preavviso