

TECNO®

www.tecnoaccessori.net

Accessori

Scheda Tecnica TC-4018WF-IP5X-TARGA

1. Product Pictures



2. Features

- 8.0 megapixel HD WiFi IP camera, maximum resolution 3840x2160;
- High-performance main control chip, good picture quality, support humanoid detection alarm and humanoid tracking;
- Support WIFI, support AP mode;
- Support up to 128G TF card storage;
- 2.7-13.5mm 5X optical zoom auto focus lens;
- 8pcs array infrared&white light LEDs, irradiation distance 80m, support color night vision;
- Built-in MIC and speakers, support two way audio;
- Pan tilt rotation, horizontal:350°&vertical:90°;
- Waterproof level IP66;
- Support P2P, view & anywhere & anytime;
- Elegant outline and easy installation;
- Provide android & ios APP and professional CMS PC client software;

Specifications

Model	800W	
Video	Sensor	8.0 megapixel 1/2.8" SONY415 Low Lux CMOS
	Video resolution	Main stream: 3840x2160@10fps Sub stream: 1280x720@25fps
	Video compression	H.264/H.265
	Lens	2.7-13.5mm 5X optical zoom auto focus lens
	View angle	61.4°~3.6°
	Night vision	8pcs array infrared&white light LEDs, irradiation distance 80m, support color night vision
Audio	Audio compression	G.726/G.711
	Audio code rate	8Kbps, 16bit
	Audio input/output	Built-in MIC and speakers, support two way audio
Alarm	Motion detection	Can set 4 independent detection areas, can set the sensitivity of 1-100
	Humanoid detection	Support, can be used in conjunction with motion detection to make the alarm more accurate
	Alarm linkage	Alarm mobile phone message push, Alarm recording or capture to Micro SD card, Alarm trigger sound alarm, Alarm capture sent to Email, Alarm recording or capture saved to FTP
	Alarm time	All day or manually customize alarm time period
Interface	Power	5.5*2.1mm power interface
	Ethernet	RJ45 Ethernet interface
	Reset button	Support, press for 5 seconds to reset the camera
	Micro SD card	Support up to 128G micro SD card
	Wireless	IEEE 802.11 b/g/n
	Onvif protocol	Support ONVIF 2.4(backward compatible)
PTZ	Rotation angle	Horizon: 350°, Vertical: 90°
	Horizontal speed	6°-25°/S
	Vertical speed	3°-15°/S
	Preset	8 preset points, supports cruise function

General specification	Power consumption	Day: 4W, Night: 17W
	Operating environment	Environment -20°C~+60°C(-4°F~+140°F), Humidity 10%~90%, non-condensing
	Shell material	Metal shell
	Waterproof level	IP66
	Product size	190mm×130mm×235mm(L×W×H)
	Product weight	1.4kg
	Package size	205mmx205mmx25mm(L×W×H)
	Package weight	2.0kg

