



Scheda Tecnica

Telecamera TECNOACCESSORI® modello TC-7020C-4in1-5mp



Main Feature:

Features:

- *Use JK-K05MP CMOS, captured moving images.
- *Support 4 in 1 Coaxial high-definition output, with excellent performance, clear and bright picture
- *Lux: 0.05Lux@(F1.2,AGC ON), 0LUX with IR
- *Support IR-CUT, CDS external control , D/N,
- *Support OSD and Customization
- *Adaptive Digital Noise Reduction, 2D-DNR
- *Support UTC
- * The Camera include 2 Lights , 2pcs warm Lights, day and night colorful.

Specification

Spec.:

| | |
|-------|---|
| Model | TC-7020C-4in1-5mp |
| Spec. | 5MP 4 in 1 coaxial high-definition CCTV camera Module |

| Detailed Specifications | |
|--------------------------------|--------------------------------------|
| Sensor | 1/2.5 " JX-K05 |
| System | PAL/NTSC |
| Effective pixels | 2608(H)x1952(V) |
| Illumination | 0.05Lux@(F1.2,AGC ON) , 0LUX with IR |
| Lens | 3.6mm |
| Shutter | AUTO |
| D/N | EXT (Default) /COLOR/B/W 20-25M |
| Synchronously | Internal |
| FPS | 5.0MP@20fps / 5.0MP@15fps |
| Video output | AHD/TVI/CVI/CVBS optional |
| OSD menu | |
| Exposure | BRIGHTNESS /EXPOSURE MODE /GAIN |
| BW | ATW/MWB |
| D/N MODE | Infrared/COLOR/B&W |
| Video Setting | Contrast/Sharpness/COLOR GAIN/DNR |
| Language | CHINESE/ENGLISH |
| Reset | |
| Common | |
| Operation Temperature | -20° to 60° |
| Operation humidity | Relative humidity less than 90 % |
| Power | DC12V(±20%) - 65MA |

OSD Switch: Default signal is AHD, switch from OSD Menu.

OSD Key to switch the signal

UP:**AHD** DOWN:**CVI** LEFT:**TVI** RIGHT : **CVBS** (Press the button with 5 seconds to switch the signal)

System Switch : PAL/NTSC directly from OSD Menu

