

Scheda Tecnica Telecamera TECNOACCESSORI® modello TC-9911C-4in1-8mp



Main Feature:

Features:

- *8MP IMX415 CMOS, captured moving images.
- *Support 4 in 1 Coaxial high-definition output, with excellent performance, clear and bright picture
- *Lux: 0.01Lux@(F1.2,AGC ON), OLUX with IR
- *Support IR-CUT, CDS external control, D/N,
- *Support OSD and Customization menu
- *Support DWDR
- *Support 6-15V wide power range supply
- *6KV lighting protect, big capacitor
- *Adaptive Digital Noise Reduction, 2D-DNR
- *Support UTC
- * The Camera include 2 Lights , 2pcs warm Lights, day and night colorful.

Specification

Model	TC-991	1C-4in1-8mp	
Spec	8MP 4	in 1 coaxial HD CCTV camera	
Detailed Specifications			
Sensor		1/2.8" IMX415+TP3818	
System		PAL/NTSC	
Effective pixels		3480(H)x2160(V)	
Illumination		0.01Lux@(F1.2,AGC ON), 0LUX with IR	
Lens		3.6mm	
Shutter		AUTO	
D/N		EXT (Default) /COLOR/B/W 20-25M	
Synchronously		Internal	
FPS		800M PAL:12.5fps / NTSC:15fps	
Video output		AHD/TVI/CVI/CVBS (Optional)	
OSD menu			
Exposure		BRIGHTNESS /EXPOSURE MODE /GAIN/DWDR	
BW		ATW/MWB	
D/N MODE		COLOR/AUTO	
Video Setting		Contrast/Sharpness/COLOR GAIN/DNR/MIRROR	
Common			
Operation		-20□ to 60□	
Temperature			
Operation humidity		Relative humidity less than 90 %	
Power		DC12V(±20%) - 60MA	

OSD Switch: Default signal is AHD, switch from OSD Menu.

OSD Key to switch the signal

UP:AHD DOWN:CVI LEFT:TVI RIGHT: CVBS (Press the button with 5 seconds to switch the signal)

System Switch: PAL/NTSC directly from OSD Menu

