



Scheda Tecnica

	Model	TC-NVR5MP16
System	Main processor	Hi3536D
	Operating System	Embedded Linux
	System Resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Operator Interface	Operator interface	16-bit true color graphic menu operation interface, support mouse operation
	Preview	1/4/8/16
Video	Video input (IP)	16*5M/16*960P
	Video standards	PAL(625TVL,50f/s); NTSC(525TVL,60f/s)
	Video compression	H.265/H.264
	Display quality	Max:4K
	Playback quality	5M/3M/960P
	Decode	2*5M/4*3M/4*960P
	Motion detection	Depend on camera
Audio	Audio compression	G.711A
	intercom	Unsupport
Record & playback	Recording mode	Manual>Alarm>Video Detection>Continuous
	Local Playback	2*5M/4*3M/4*960P
	Search mode	search by Time/calendar/event/channel
Storage &	Record Storage	HDD 、 network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
	Video output	1ch HDMI HD output(Customized VGA interface)
	Network interface	1*RJ45 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 port
	Hard disk	1*SATA(Up to 6TB for each disk)
other	PTZ control	Control PTZ device by network
	ONVIF	Support
	Power supply	12V/2.5A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0℃-+55℃ , Humidity:10%-90%RH , Atm:86kpa-106kp
	weight	Around 100g



A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni senza preavviso