

Scheda Tecnica Telecamera TECNOACCESSORI® TC-2214WF-IP (Ver. App. iCSee/XMEye)



- ◆ **APP:XMEye / Csee**
- ◆ P2P technology , plug and play : no any settings
- ◆ Support multiple platforms, terminals, networks
- ◆ Clear and fluent video ,Fastest Intelligent Transfertation
- ◆ Financial-level security control to ensure privacy
- ◆ Support remote firmware upgrade
- ◆ Smart transmission technology: adaptive bandwidth, dynamic code rate adjustment, voice first, the jitter buffer.
- ◆ Support two-way audio, telecommunication level of signal processing, (echo cancellation, noise suppression, comfort noise, silence suppression)
- ◆ Support Android /iOS system mobile devices, remote real-time monitoring(25 fps image transmission, 1080P HD images)
- ◆ Motion detection, real-time App push notifications
- ◆ High Definition 1920*1080,clear image
- ◆ 12 pcs infrared LEDs, night vision distance: 10 meters, 24 hours day and night monitoring, IR-CUT switch
- ◆ Support WIFI(IEEE802.11b/g/n),Support WPS one key Wi-Fi configuration
- ◆ Support micro SD card (max 64 GB) storage,Cloud box local recorde and cloud storage
- ◆ Support QR code login
- ◆ Support Pan and Tilt (level: 355° & vertical: 90 °)

Specifications

Image sensor	Image sensor	1/3 "color CMOS sensor
	Display resolution	1920 *1080 (1080P)
	Lens	f: 3.6mm, F:2.0
	Viewing angle (horizontal)	55°
	Minimum illumination	0.5Lux
Audio	Input/output	Two-way audio (built-in microphone and speaker)
	Audio compression	AAC(Advanced Audio Coding)
Video	Video compression	H.265X
	Lighting frequency	50Hz, 60Hz
	Image frame rate	25fps
	Image resolution	HD1080P(1920*1080), 640*360
	Image adjustment	Brightness, Contrast, Saturation, Sharpness
	White balance, BLC	Automatically
Internet	Night vision	12 infrared LEDs, IR distance: 10 meters
Alarm	Wireless networks	WiFi(IEEE802.11b/g/n), Built-in antenna
	Alarm Detection	Motion detection Snapshot, audio/video record
	Alarm linkage	Support snapshot, audio / video
Interface	Alarm notification	Real-time App push notifications
	power	1DC 5V / 2.0 A, power consumption < 7W
	Buttons	A reset button, a WPS (WiFi Protected Setup) button
	Network interface	1*RJ45 10/100M adaptive Ethernet port;
Others	WiFi	Built-in antenna
	pan & tilt	Level: 355° & vertical: 90°
	LED instructions	Network signal/power/network function
	Video storage	Micro SD card (max 64 GB) storage, mini NVR and cloud storage
	Work temperature	0° ~ 55°C (32°F ~ 131°F)

Environment	Work humidity	10% ~ 80% (No condensation)
	Storage temperature	-10°C ~ 60° (14°F ~ 140°F)
	Storage humidity	0% ~ 90%(No condensation)
Size	Size(L*W*H)	
	Net weight	



A causa di countinua evoluzioni tecniche del prodotto , le caratteristiche possono subire variazioni senza preavviso