Scheda Tecnica

Telecamera Tecnoaccessori® modello TC-7021-4in1 5MP

New Super HD 5MP AHD Camera Waterproof Security Camera AHD System Video Surveillance With Bracket

1 FH8538M+K03 CMOS FOR 5MP
2.The Resolution is: 5MP 2560(H)*1920(V)
3.36PCS IR LEDS with 30M IR Distance
4. Built in IR-CUT Filter, Day & Night Vision
5. High Quality Metal Case, Used Outdoor, Waterproof IP66
6. Standard lens: HD 2.8-12mm Lens .
7.AHD (Analog High Definition), a new video format for enhanced CVBS (COMET*) & HD video transmission.
8. HD AHD camera is an over-coaxial-cable analog HD video transmission standard, allowing long-distance HD transmission at a lower cost to meet the requirements for a complex and large installation.
9. Usually use Coaxial-Cable, SYV-75-5 cable can transfer video over 500meters.
10. MUST work with 5MP AHD DVR
11. Best choice for project reconstruction.
12. You can upgrade an old analog security system to HD cameras without changing cable routes.

Model	TC-7021-4in1-MVF
Image Sensor	1/2.7 inch K03 CMOS

DSP	FH8538M HD DSP
Signal System	PAL/NTSC
Min Illumination	Colour:0.1Lux/F1.2 B/W:0.01Lux/F1.2 IR-ON:0Lux
S/N Ratio	>58dB(AGC OFF)
Video Output	1CH AHD HD/CVBS Standard Singal Output(Switchable)
Max Transmission Distance	Over 500m via 75-3 coaxial cable(Don't use inferior cables)
Infrared LED	36pcs IR Led 35M
IR Distance	36 Meters (The difference of scene environment will lead to differences of IR distance)
Day&Night	IR cut filter with auto switch
Lens	Default 2.8-12mm
Image	
Max Resolution	2560(H)*1920(V)
Image Process	AE, AWB, ABF, ABLC
2DNR/3DNR	Support(Auto)
Interface	
Communication Interface	1Vp-p Composite Output(75Ω/BNC）
Power port	1*DC12V(5.5mm/2.1mm)
General	
Reliability	Comprehensive lightning protection,in line with national and international standarda;7*24 hours 65 ℃ high temperature stable and reliable testing (camera board testing)
Operating Environment	-10°~60°,humidity 90% or less (non-condensing)
Power Supply	DC12V ± 10%
Power Consumption	Max.6W
Housing Material	Metal

A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni