

**SCHEDA TECNICA**  
**Telecamera Tecno modello TC-2008-I36ip-PoE**

<b>Model NO.</b>		
<b>Hardware</b>		
Main Chipset	Hi3516C	
Image Sensor	1/2.8" Sony EXMOR progressive scan CMOS	
Effective Pixels	2.0MP	
<b>Interface</b>		
Optical lens	Infrared Light	36 pcs IR LEDs
	Focal Length	3.6/4/6/8/12mm optional
Audio/intercom input	optional	
Audio output	optional	
Network Interface	Lan	10/100/1000M BASE-TX,RJ-45 connector
RS485	RS485 port Optional	
Alarm I/O	1ch Alarm input or 1ch alarm output (optional)	
Memory Slot	optional(support 32GB)	
<b>Audio&amp;Video encoding</b>		
Video Compression	H.264 Main Profile; MJPEG Baseline	
Video Bitrate	30Kbps~16Mbps,Supports CBR/VBR	
Video output	1ch BNC analogue (optional)	
Title OSD Settings	Supports channel name, date, and video stream information overlay; OSD location is adjustable	
Auto Image Control Functions	Auto Exposure Control (AEC), Auto White Balance (AWB),Auto Gain Control(AGC),Digital Noise Reduction(DNR)	
Manual Image Controls	Color saturation, hue, gamma, sharpness (edge enhancement),	
Others	Anti Fogging/Anti Trembling/IR Detection/IRIS	
Audio Compression	G.711A	
<b>Data transmission and storage</b>		
Data storage	Video and Image	
Recording	Recording set up to record by Auto or manual (motion and alarm trigger, schedule)	
Alarm Output	FTP,E-mail	
Network protocol	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
ONVIF protocols	Support 2.0 Above version	
Remote View	PC	IE 6.0 Above; firefox;Google Chrome
	Mobile Phone	Support iPhone, Android system
<b>General Parameters</b>		
Environmental Casing	Metal, Outdoor	
Operating Temperature	-10 ° C ~ 50 ° C	
Operating Humidity	0% -85% RH	
Power	DC12V ±10%	
<b>POE</b>	<b>Support</b>	
Power Consumption	<5W	
Dimension		
Weight		



A causa di continua evoluzione dei Prodotti Le Caratteristiche possono subire variazioni